

Are Your Critical Messages Secure?



Now They Will Be **Introducing the Unication Elite Secure Pager**

- **Secure Messaging**
Encrypted messages cannot be decoded.
- **Improved Efficiency**
Send all necessary information.
- **Message Lock**
Messages are automatically locked and can only be read by entering a password.
- **Narrow Band Auto Migration**
Automatically detects narrow or wide band networks.



Unication Elite Secure+

Elite Secure+

Protocol	FLEX	
Band Split	VHF	900 MHz
Frequency Range	143-153 MHz	929-932 MHz
	153-163 MHz	
	163-174 MHz	
Baud Rate (bps)	1600/ 3200/ 6400 bps	
Paging Sensitivity	1600: <= 8 u/Vm 3200: <= 11 u/Vm 6400: <= 13.5 u/Vm	
Selectivity	>= 55 dB	>= 50 dB
Spurious & Image Rejection	>= 40 dB	
Frequency Stability	<= +/-15 ppm	<= +/-3.5 ppm
Channel Spacing	12.5/ 25 KHz	25 KHz
Receiver Type	Synthesized	
Address Capability	16 FLEX Addresses	
Frequency Deviation	+/-4.8 KHz	
Alert Tone SPL	78 dB @ 12 in (2700 Hz Standard Alert)	
Operating Temperature	5° to 40°C (40° to 105°F)	
Storage Temperature	-40° to 85°C	
Battery	1.5V Single AA Alkaline Battery	
Battery Life	Auto Baud Detect Collapse=4 90 days	
Low Battery Alert Level	1.24 Volts (Programmable)	
Weight	87.5g (3.1oz)	
Dimension	81 X 55 X 18.5 mm (3.19 X 2.16 X 0.73 inch)	
UL Rating	Class 1, Division II, Groups A,B,C,D.	

*Estimated battery life is based on full battery capacity and 2 pages/ day

**WHEN YOU SERVE TO SAVE LIVES
UNICATION SERVES YOU**

Head Office

Unication CO., Ltd.
Tel.: +886-2-2299-9678
Address: 5F., No.6, Wu-Kung 5Rd.,
Hsinchuang District, New Taipei City, Taiwan
Email: salesenquiry@uni.com.tw

North America Branch Office

Unication USA Inc.
Tel.: +1-817-303-9320
Address: 1901 E. Lamar Blvd.,
Arlington, TX 76006, U.S.A.
Email: sales@unication.com



Unication

www.unication.com