




FEATURES	V10MR MURS	F3001 F4001	F1000 F2000	F1000S F2000S
				
Channels	16	16	16	128
Power Output (VHF/UHF)	2W	5W/4W	5W/4W	5W
Frequency Coverage (VHF/UHF)	151-154 MHz	136-174 MHz 400-470, 450-512 MHz	136-174 MHz 400-470, 450-512 MHz	136-174 MHz 400-470, 450-512 MHz
MDC Signaling		Limited	Limited	Basic
Tone Signaling		Yes	Yes	Yes
Battery Operating Time	16*	14 NiMH*/ 20 Li-Ion*	14*	14*
IP Waterproof Rating	IP67	IP54	IP67	IP67
Keypad				4 Key
Connector Pin Type	2	2	2	2
Built-in Inversion Voice Scrambler			Yes	Yes
Channel Announcement	Yes		Yes	Yes
MISC (Surveillance Function, Low Battery Alert, Voice & Vibrate Function)	Low Battery Alert Surveillance Function	Low Battery Alert Surveillance Function	Low Battery Alert Surveillance Function	Low Battery Alert Surveillance Function
MOTOROLA®	VX-261	VX-261	VX-261	CP185 VX-264
KENWOOD®	NX-P1202AV/P1302AU	NX-1200AV/1300AU	NX-1200AV/1300AU	NX-1200AV/1300AU

Legend

Good	Better	Best	No
			

*Typical operation Tx:Rx: Stand-by = 5:5:90, power save ON.

**Version available

©2021 Icom America Inc. The Icom logo is a registered trademark of Icom Inc. The IDAS name and logo are trademarks of Icom Inc. All other trademarks remain the property of their respective owners. At-A-Glance is for comparison and training purposes only, and is based on current brochures available at the time of printing. All data should be confirmed by the reader prior to making any decisions or drawing any conclusions. Current product information may be procured from the appropriate manufacturer. No fitness of purpose for any specific application is claimed or asserted in this comparison. 43056

AIR. LAND. SEA.