



U.S. Marine Retail Price Book

July 2024



All stated specifications are subject to change without notice or obligation.
All Icom radios meet or exceed FCC regulations limiting spurious emissions.
© 2024 Icom America Inc. The Icom logo is a registered trademark of Icom Inc.
All other trademarks remain the property of their respective owners.

Icom America Inc.

Contents

VHF Handhelds	3
M25	4
M37	6
M73	8
M85	10
M85UL	13
M94D	15
VHF Fixed Mount.....	17
M330 – M330G	18
M400BB	20
M4100BB & M510BB	22
M424G	24
M510	26
M510 EVO	28
M605	30
HM195/G.....	33
SSB	34
M803	35
GMDSS	37
GM1600	38
AIS & Radars.....	40
MA510TR.....	41
MR-1010R2.....	43
Discontinued Radios.....	45
M93D	46
M36	47
M604	48
M802	50
M506	51

VHF Handhelds



M25

VHF Floating Handheld

SPECS

Output Power:	5W, 1W
Waterproof Rating:	IPX7 (submersible protection)
Frequencies:	Tx: 156.025–157.425MHz Rx: 156.050–163.275MHz
Usable Channel Groups:	INT, USA, CAN and WX
Type of Emission:	FM (16K0G3E)
Current Drain (at 3.7V DC):	Tx (High): 2.3A Rx (at AF max): 300mA/200mA
Weight:	7.8oz
Versions:	Marine blue Metallic black



FEATURES

- Float 'n flash
- USB charging
- 11 hours battery life
- Large LCD with simple user interface (30% larger than M24)
- 550mW audio output
- 4-step battery life indicator
- Dual/Tri-watch functions
- Weather channel with weather alert
- Instant access to Ch. 16 or programmable call channel
- Auto scan function
- Tag scan
- Favorite channel functions
- Monitor function opens noise squelch
- LCD auto backlighting
- AquaQuake draining function

COMES WITH

- Battery charger (BC217SA)
- Belt clip (MB133)
- Antenna (FASC59V)
- Hand strap
- Owner's manual
- Warranty: 3 years

IPX7

M25

VHF Floating Handheld

Configurations

Model	Description	MSRP
M25 BLACK 41 USA	5W floating marine VHF handheld in metallic black	\$203.00
M25 BLUE 51 USA	5W floating marine VHF handheld in marine blue	\$203.00

Accessories

Model	Description	MSRP
Antennas		
FASC59V	Standard antenna M25/M37/M93D/M92D	\$24.00
Batteries		
BP282	1500mAh Li-ion battery for the M25	\$54.00
Belt Clips		
MB133	Alligator type belt clip	\$18.00
Chargers		
BC217SA	USB charger; 100-240V with a US style plug	\$23.00
Microphones		
HM213	Waterproof floating speaker mic for M25	\$126.00
Software & Cables		
CSM25	M25 programming software (requires OPC478UC+OPC1655)	\$0.00
OPC1655	Cloning cable adapter for M25/M36/M37/M93D/M94D	\$50.00
OPC478UD	USB programming cable (2-pin connectors handhelds)	\$95.00

M37

VHF Floating Handheld

SPECS

Output Power:	6W, 1W
Waterproof Rating:	IP57 rating
Frequencies:	Tx: 156.025-157.425MHz Rx: 156.050-163.275MHz
Usable Channel Groups:	INT, USA, CAN, WX
Type of Emission:	16K0G3E
Current Drain:	Tx (at 6.0W/1.0W output): 2.5A/1.0A Rx (Max audio. Inter SP/Exter SP): 0.4A/0.2A
Weight:	10.3oz (with BP296)



FEATURES

- 700mW audio output
- Channel history function stores the last five channels used for easy recall
- Float'n Flash function
- Low Battery Alert function
- Voice Loud and Mute function enables to temporary maximize/mute the volume
- AquaQuake™ function prevents audio degradation from a water-logged speaker
- Dualwatch and Tri-Watch functions
- Favorite Channel function
- Instant access to channel 16 and the Call channel
- Weather channels with Weather Alert function

COMES WITH

- Battery pack (BP296)
- Trickle charger (BC235)
- AC adapter (BC217SA)
- Belt clip (MB133)
- Antenna (FASC59V)
- Hand strap
- Owner's manual
- Warranty: 3 years



M37

VHF Floating Handheld

Configurations

Model	Description	MSRP
M37 31 USA	6W marine VHF floating handheld with battery, charger included	\$299.00

Accessories

Model	Description	MSRP
Antennas		
FASC59V	Standard antenna M25/M37/M93D/M92D	\$24.00
Batteries		
BP296	3.6V 2350mAh Li-Ion battery (M37)	\$79.00
BP297	Alkaline case for M37 (3 x AAA)	\$33.00
Belt Clips		
MB133	Alligator type belt clip	\$18.00
Chargers		
BC217SA	USB charger; 100-240V with a US style plug	\$23.00
BC235	Desktop trickle charger (requires BC217SA)	\$23.00
BC238	6-unit gang charger for the M37	\$459.00
Microphones		
HM213	Waterproof floating speaker mic for M25	\$126.00
Software & Cables		
OPC1655	Cloning cable adapter for M25/M36/M37/M93D/M94D	\$50.00
OPC478UD	USB programming cable (2-pin connectors handhelds)	\$95.00

M73

VHF Submersible Handheld

SPECS

Output Power:	6W, 3W, 1W
Waterproof Rating:	IPX8 (submersible)
Frequencies:	Tx: 156.025-157.425MHz Rx: 156.050-163.275MHz
Usable Channel Groups:	INT, USA, CAN, WX
Type of Emission:	FM (16K0G3E)
Current Drain:	Tx (at 6W output): 1.5A Rx (Max.audio): 450mA/250mA
Weight:	11.3oz (with BP245N)



FEATURES

Both Versions:

- Slim, hourglass body and wide viewing angle LCD
- IPX8 Submersible Plus™
- 700mW loud audio
- 6W RF output power
- AquaQuake™ water draining function
- Dual/Tri-Watch function for monitoring Channel 16 and/or call channel
- 4 level battery indicator
- Favorite channel and tag scan functions
- Auto power save function

Plus Version:

- Last call voice recording
- Base boost function
- Bidirectional active noise cancelling

COMES WITH

- Antenna (FAS64V)
- Battery pack (BP245N)
- Belt clip (MB103)
- Cigarette lighter cable (CP25H)
- Rapid charger (BC210)
- Hand strap
- Owner's manual
- Warranty: 3 years



M73

VHF Submersible Handheld

Configurations

Model	Description	MSRP
M73 61 USA	6W IPX8 submersible handheld	\$331.00
M73 PLUS 71 USA	6W IPX8 submersible handheld with built-in active noise cancelling, base boost function, and voice recording	\$410.00

Accessories

Model	Description	MSRP
Antennas		
AD92SMA	Antenna connector adapter to connect a BNC-type antenna	\$22.00
FAS64V	Standard antenna for the M72/M73 (4 17/32" or 115mm)	\$18.00
Batteries		
BP245H	7.4V 2000mAh Li-Ion battery for M72/M73	\$123.00
Belt Clips		
MB103	Alligator belt clip	\$14.00
MB86	Swivel belt clip that screws into back of radio	\$14.00
MB96N	Swivel belt hanger to use with belt clip	\$40.00
Cables		
OPC515L	DC power cable for single unit rapid chargers	\$28.00
Chargers		
AD129	Adapter cup for BC197 gang charger for M73	\$28.00
BC123SA	Straight-angle AC adapter for rapid chargers; 100-240V with US style plug	\$26.00
BC123SE	AC adapter for rapid chargers; 100-240V with Euro style plug	\$28.00
BC157S	AC adapter for gang chargers; 100-240V with US style plug	\$168.00
BC157SE	AC adapter for gang chargers; 100-240V with Euro style plug	\$168.00
BC210	Rapid charger for the BP-245 includes AC adapter with US plug	\$84.00
CP23L	12V cigarette lighter cable for use with rapid chargers	\$40.00
Headsets		
HS94	Earpiece headset; use with VS/OPC2004/OPC2006/OPC1392	\$27.00
HS95	Headset with boom mic; use with VS/OPC2004/OPC2006/OPC1392	\$230.00
HS97	Earphone with throat mic headset; use with VS/OPC2004/OPC2006/OPC1392	\$45.00
OPC1392	Headset adapter to use with HS94/95/97 for the M73/M72/GM1600/M90	\$81.00
Microphones		
HM167	Lightweight IPX8 waterproof speaker mic M73/GM1600/M92/M72	\$131.00
HM202	Compact IPX7 waterproof speaker mic M73/M72	\$139.00
Software & Cables		
CSM73	Programming software for the M73	\$0.00
OPC478UD	USB programming cable (2-pin connectors handhelds)	\$95.00
OPC922	Cloning cable adapter for M72/M73/M92D	\$68.00

M85

VHF Dual Band Handheld

SPECS

Output Power:	
Marine:	5W, 3W, 1W
Land mobile:	2W, 1W
Waterproof Rating:	IP67
Frequencies:	
Marine Tx:	156.025-157.425MHz
Marine Rx:	156.050-163.275MHz
LMR Tx/Rx:	136.000-174.000MHz
Usable Channel Groups:	USA, INT,CAN, WX 100 LMR
Type of Emission:	
Marine	16K0G3E
LMR	16K0F3E 11K0F3E
Current Drain:	Tx (at 5W output): 1.5A Rx (at AF max): 0.45A
Weight:	8.7oz



FEATURES

- Compact and lightweight
- Covers 136-174MHz land mobile frequency
- Up to 100 programmable land mobile channels
- 700mW loud audio
- Three emergency functions: MOB alarm, Man Down, and Lone Worker
- Multi-function button allows user to change from marine to land mobile channels or use the scrambler function
- Buil-in voice scrambler (32-code)
- AquaQuake™
- Internal VOX capability
- Weather channel receiving
- Priority scan
- Dual/Tri-watch function for monitoring CH16 and/or call channels

COMES WITH

- Battery pack (BP290)
- Battery charger (BC227)
- AC adapter (BC123SA)
- Antenna (FAS58V)
- Belt clip (MBB3)
- Hand strap
- Owner's manual
- Warranty: 3 years

M85

VHF Dual Band Handheld

Configurations

Model	Description	MSRP
M85 21 USA	Marine VHF 5W handheld; 100 land mobile programmable channels (2W). Antenna (FASC58V), battery (BP294), and charger (BC227/BC123SA) included.	\$494.00

Accessories

Model	Description	MSRP
Antennas		
FASC58V	Standard antenna M24/M34/M36/M85	\$18.00
Batteries		
BP291	Battery case 5 x AA	\$53.00
BP294	3150mAh li-ion battery for the F52D/F62D/M85	\$130.00
Belt Clips		
MB136	Swivel belt clip for F1000/F3400/F7010/F52D/M85 series	\$16.00
MB96N	Swivel belt hanger to use with belt clip	\$40.00
MBB3	Standard belt clip	\$17.00
Cables		
OPC515L	DC power cable for single unit rapid chargers	\$28.00
Carrying Cases		
LCF1052S	Leather case with swivel belt loop and D-ring for the F52D	\$52.00
NCF1052C	Nylon case for the F52D with a clip	\$32.00
Chargers		
BC123SA	Straight-angle AC adapter for rapid chargers; 100-240V with US style plug	\$26.00
BC123SE	AC adapter for rapid chargers; 100-240V with Euro style plug	\$28.00
BC157S	AC adapter for gang chargers; 100-240V with US style plug	\$168.00
BC157SE	AC adapter for gang chargers; 100-240V with Euro style plug	\$168.00
BC214-1	Six gang charger (includes AC adapter with US plug)	\$541.00
BC214-1E	Six gang charger (includes AC adapter with Euro plug)	\$541.00
BC225	Smart rapid charger; 100-240V with a US style plug	\$142.00
BC226	Connectable rapid charger (connect up to 6). Requires AC adapter: BC123S for single use or BC228 for 2+	\$80.00
BC227	Rapid charger that goes into trickle mode at a 80% charge (US Plug)	\$72.00
BC228	AC adapter for connectable chargers (BC226, BC202IP3, & BC257). Use one BC228 for up to 4 BC257's, 6 BC202IP3 or BC226 chargers.	\$79.00
CP23L	12V cigarette lighter cable for use with rapid chargers	\$40.00
Headsets		
HS94	Earpiece headset; use with VS/OPC2004/OPC2006/OPC1392	\$27.00
HS95	Headset with boom mic; use with VS/OPC2004/OPC2006/OPC1392	\$230.00
HS97	Earphone with throat mic headset; use with VS/OPC2004/OPC2006/OPC1392	\$45.00
VS5MC	VOX/PTT switch cable to use with headset (HS94/95/97)	\$161.00
Microphones		
HM184H	14-pin loud waterproof speaker mic (no accessory jack)	\$126.00

M85

VHF Dual Band Handheld

Accessories

Model	Description	MSRP
HM222H	IP68 waterproof speaker microphone w/3.5mm accessory jack (14-pin connector)	\$165.00
HM236	Compact waterproof speaker microphone	\$133.00
HM-HD7I6WP	Large waterproof, high gain speaker microphone with 3.5mm accessory jack (14-pin connector)	\$130.00
SP27	Acoustic tube earphone with a clip (3.5mm)	\$38.00
SP29	Earhook type earphone with 3.5mm plug	\$27.00
SP40	Earphone with 3.5mm plug	\$32.00
SP-AT1	Single pin listen only w/QD acoustic tube (9", 3.5mm L-shape)	\$34.00
Miscellaneous		
AD118	14-pin ACC adapter to use with Hirose plug accessories	\$86.00
AD135	3.5mm earphone jack adapter that plugs into a 14-pin connector	\$45.00
Software & Cables		
CSM85	M85 programming software	\$0.00
RSBC225	Battery management software for the BP-283/284/BP290. Can connect up to 30 BC-225 chargers to it.	\$263.00
Wire Kits		
EH15B	Earphone with 2.5mm plug to use with HM-163MC	\$33.00
HM163MC	Lapel mic with 2.5mm earphone jack	\$210.00
SP26	Tube earphone with 2.5mm plug to use with HM-163MC/HM-153LS	\$27.00
SP28	Earhook type earphone with 2.5mm plug to use with HM-163MC/HM-153LS	\$27.00
SP32	Tube adapter for use with the EH-15B	\$32.00

M85UL

VHF Intrinsically Safe Marine Handheld

SPECS

Output Power:	
Marine:	5W, 3W, 1W
Land mobile:	2W, 1W
Waterproof Rating:	IP67
Frequencies:	
Marine Tx:	156.025-157.425MHz
Marine Rx:	156.050-163.275MHz
LMR Tx/Rx:	136.000-174.000MHz
Usable Channel Groups:	USA, INT,CAN, WX 100 LMR
Type of Emission:	
Marine	16K0G3E
LMR	16K0F3E 11K0F3E
Current Drain:	Tx (at 5W output): 1.5A Rx (at AF max): 0.45A
Weight:	8.7oz



FEATURES

- Compact and lightweight
- Covers 136-174MHz land mobile frequency
- Up to 100 programmable land mobile channels
- 700mW loud audio
- Three emergency functions: MOB alarm, Man Down, and Lone Worker
- Multi-function button allows user to change from marine to land mobile channels or use the scrambler function
- Buil-in voice scrambler (32-code)
- AquaQuake™
- Internal VOX capability
- Weather channel receiving
- Priority scan
- Dual/Tri-watch function for monitoring CH16 and/or call channels
- Intrinsically Safe: meets ANSI/TIA-4950-A, ANSI/UL 121201 requirements for:
 - Intrinsically safe: Class I, Division 1, Groups C, D;
 - Class II, Division 1, Groups E, F, G;
 - Class III. T3C.
 - Non-incendive: Class I, Division 2, Groups A, B, C, D

COMES WITH

- Battery pack (BP292IS)
- Battery charger (BC227)
- AC adapter (BC123SA)
- Antenna (FAS58V)
- Belt clip (MBB3)
- Hand strap
- Owner's manual
- Warranty: 3 years

M85UL

VHF Intrinsically Safe Marine Handheld

Configurations

Model	Description	MSRP
M85UL 31 USA	Intrinsically safe marine VHF 5W handheld; 100 land mobile programmable channels (2W). Antenna (FASC58V), battery (BP292UL), charger (BC227/BC123SA) included.	\$641.00

Accessories

Model	Description	MSRP
Antennas		
FASC58V	Standard antenna M24/M34/M36/M85	\$18.00
Batteries		
BP292UL	2010mAh li-ion intrinsically safe battery	\$289.00
Belt Clips		
MB136	Swivel belt clip for F1000/F3400/F7010/F52D/M85 series	\$16.00
MB96N	Swivel belt hanger to use with belt clip	\$40.00
MBB3	Standard belt clip	\$17.00
Cables		
OPC515L	DC power cable for single unit rapid chargers	\$28.00
Carrying Cases		
LCF1052S	Leather case with swivel belt loop and D-ring for the F52D	\$52.00
Chargers		
BC123SA	Straight-angle AC adapter for rapid chargers; 100-240V with US style plug	\$26.00
BC123SE	AC adapter for rapid chargers; 100-240V with Euro style plug	\$28.00
BC157S	AC adapter for gang chargers; 100-240V with US style plug	\$168.00
BC157SE	AC adapter for gang chargers; 100-240V with Euro style plug	\$168.00
BC214-1	Six gang charger (includes AC adapter with US plug)	\$541.00
BC214-1E	Six gang charger (includes AC adapter with Euro plug)	\$541.00
BC226	Connectable rapid charger (connect up to 6). Requires AC adapter: BC123S for single use or BC228 for 2+	\$80.00
BC227	Rapid charger that goes into trickle mode at a 80% charge (US Plug)	\$72.00
BC228	AC adapter for connectable chargers (BC226, BC202IP3, & BC257). Use one BC228 for up to 4 BC257's, 6 BC202IP3 or BC226 chargers.	\$79.00
CP23L	12V cigarette lighter cable for use with rapid chargers	\$40.00
Microphones		
HM184UL	14-pin intrinsically safe approved waterproof speaker mic (no accessory jack)	\$215.00
Software & Cables		
CSM85	M85 programming software	\$0.00
RSBC225	Battery management software for the BP-283/284/BP290. Can connect up to 30 BC-225 chargers to it.	\$263.00

M94D

VHF AIS Handheld

SPECS

Output Power:	6W
Waterproof Rating:	IPX7
Frequencies:	Tx: 156.025-157.425 MHz Rx: 156.050-163.275 MHz
Usable Channel Groups:	INT, USA, CAN, WX
Type of Emission:	FM (16K0G3E) DSC (16K0G2B) AIS (16K0GXW)
Current Drain:	Tx (6W/1W output): 1500mA/700mA Rx (Inter SP/Exter SP Max audio): 700mA/350mA
Weight:	12.6 oz (with BP306 and antenna)



FEATURES

- Built-in AIS and DSC
- Simplified navigation system
- Up to 50 plottable waypoints
- Up to 10 hours of battery life
- Active noise cancelling technology
- Float'n Flash
- Aquaquake™ draining function
- Dualwatch and Tri-watch functions
- Supports 4-digit channels
- Weather channel receive
- Favorite 4-digit channels

COMES WITH

- Antenna (FASC59V)
- Battery pack (BP306)
- Battery charger (BC251)
- AC adapter (BC242)
- Belt Clip (MB-133)
- Hand strap

IPX7



M94D

VHF AIS Handheld

Configurations

Model	Description	MSRP
M94D 21 USA	6 Watt VHF transceiver with built-in AIS & DSC.	\$510.00

Accessories

Model	Description	MSRP
Antennas		
FASC59V	Standard antenna M25/M37/M93D/M92D	\$24.00
Batteries		
BP306	Battery pack for the M94D	\$126.00
Belt Clips		
MB133	Alligator type belt clip	\$18.00
Chargers		
BC123SA	Straight-angle AC adapter for rapid chargers; 100-240V with US style plug	\$26.00
BC242	AC adapter	\$26.00
BC251	Rapid charger for the BP306	\$68.00
CP23L	12V cigarette lighter cable for use with rapid chargers	\$40.00
CP25H	Cigarette lighter cable to use with the BC-202IP3L rapid charger	\$29.00
Microphones		
HM165	Waterproof speaker mic for M34/M36/M93D/M94D	\$118.00
HM228	Compact IPX7 speaker mic for M93D/M94D/IP110H	\$103.00
Software & Cables		
OPC1655	Cloning cable adapter for M25/M36/M37/M93D/M94D	\$50.00
OPC478UD	USB programming cable (2-pin connectors handhelds)	\$95.00

VHF Fixed Mount



M330 – M330G

VHF Fixed Mount

SPECS

Output Power:	25W, 1W (High, low)
Waterproof Rating:	IPX7 (Waterproof protection)
Frequencies:	Tx: 156.025–161.600MHz Rx: 156.050–163.275MHz Ch70: 156.525MHz
Usable Channel Groups:	USA, CAN, INT and WX
Type of Emission:	FM (16K0G3E) DSC (16K0G2B)
Current Drain:	Tx (at 25W output): 5A Rx (AF max): 1A
Weight:	730g; 1.6lb
Versions:	Black or super white GPS or non GPS



FEATURES

- Built-in GPS receiver with a supplied GPS antenna (G version)
- Built-in Class D DSC with CH70 dedicated receiver
- Intuitive user interface
- Common NMEA interface for external GPS/NAV connection
- MA-500TR Class B AIS transponder compatible
- Tag scan and favorite channel functions
- Dual/tri-watch function for monitoring CH16 and/or call channel
- Priority scan function
- Display and keypad backlighting
- External speaker connection
- AquaQuake™ draining function

COMES WITH

- Hand microphone (HM235B/W)
- DC power cable
- Mounting bracket kit
- Owner's manual
- Warranty: 3 years

IPX7

M330 – M330G

VHF Fixed Mount

Configurations

Model	Description	MSRP
M330 BLACK	Black marine compact VHF fixed mount	\$319.00
M330 WHITE	White marine compact VHF fixed mount	\$319.00
M330G BLACK	Black marine compact VHF fixed mount with built-in GPS receiver and supplied GPS antenna	\$347.00
M330G WHITE	Super white marine compact VHF fixed mount with built-in GPS receiver and supplied GPS antenna	\$347.00

Accessories

Model	Description	MSRP
Microphones		
HM235B	Black microphone for M330	\$59.00
HM235W	White microphone for M330	\$59.00
Mounting Hardware		
MBF5	Flush mount kit for M330 series	\$35.00
Navigation		
MA510TR 13	AIS transponder with GPS navigation function, and NMEA 2000 connectivity.	\$1,418.00
Software & Cables		
CSM330	M330 programming software, includes dongle	\$0.00

M400BB

VHF Fixed Mount

SPECS

Output Power:	25W, 1W
Waterproof Rating:	IPX7 (submersible)
Frequencies:	Tx: 156.025–157.425MHz Rx: 156.050–163.275MHz Ch. 70: 156.525MHz
Usable Channel Groups:	USA, INT, CAN, WX
Type of Emission:	FM (16K0G3E) DSC (16K0G2B)
Current Drain:	Tx (at 25W output): 5.5A Rx (Max audio): 3.5A
Weight:	1.83lb (M400BB) 14.1oz (HM195B/SW)



FEATURES

- Space-saving, two-piece configuration
- New intuitive user interface
- Active noise cancelling
- 10W loud audio, public address and foghorn
- Built-in class D DSC
- Common NMEA interface
- AIS target call with MA-500TR
- MarineCommander™ compatible
- AquaQuake™ water draining function
- Dual/tri-watch function for monitoring Ch.16 and/or call channel

COMES WITH

- Commandmic (HM195B/SW)
- DC Power cable
- Owner's manual
- Warranty: 3 years

IPX7

M400BB

VHF Fixed Mount

Configurations

Model	Description	MSRP
M400BB	Black box marine VHF fixed mount with black Command Mic	\$626.00
M400BB SW	Black box marine VHF fixed mount with white Command Mic	\$626.00

Accessories

Model	Description	MSRP
External Speakers		
SP37	30W hailer/speaker for fixed mounts; 4 ohm, extra UV protecting, all stainless steel hardware, heavy duty mounting bracket	\$76.00
Microphones		
HM195B 41 EXP	CommandMic IV with yellow backlit LCD in black	\$269.00
HM195GB 61 EXP	CommandMic IV with white backlit LCD in black	\$269.00
HM195GW 62 EXP	CommandMic IV with white backlit LCD in super white	\$269.00
HM195SW 42 EXP	Command Mic IV with yellow backlit LCD in super white	\$269.00
OPC1541	6.1m/20ft extension cable to use with the COMMANDMIC III/IV with the OPC1540. Up to 2 OPC-1541 can be connected.	\$81.00
Navigation		
MA510TR 13	AIS transponder with GPS navigation function, and NMEA 2000 connectivity.	\$1,418.00
Software & Cables		
CSM400BB	M400BB programming software. Requires OPC-478UC + OPC-980 cables.	\$0.00
OPC478UD	USB programming cable (2-pin connectors handhelds)	\$95.00
OPC980	Cloning cable adapter for M424/M504/M604/M510	\$40.00

M4100BB & M510BB

VHF Fixed Mount

SPECS

Output Power:	25W, 1W
Waterproof Rating:	IPX7 (submersible)
Frequencies:	Tx: 156.025–157.425MHz Rx: 156.050–163.275MHz DSC (CH70): 15.525 MHz AIS: 161.975, 162.025 MHz
Usable Channel Groups:	USA, CAN, INT, WX channels
Type of Emission:	16K0G3E (FM), 16K0G2B DSC), 16K0GXW (AIS*)
Current Drain:	Tx: 5.5A Rx: 1.5A (One-CommandMic™) 4.0A (Two CommandMic and RX hailer) 4.5A (Three CommandMic and RX hailer)
Weight:	1.9 lbs (M4100BB) 2 lbs (M510BB)

* Only on the M510BB



FEATURES

- Remote CommandMic stations: up to two (M410BB) or three (M510BB)
- CommandMic intercom function
- Class D DSC
- NMEA 0183® -HS
- NMEA 2000®
- One-way RX hailer and foghorn function
- Active noise cancelling
- Anchor watch function
- AquaQuake™ Anchor watch function
- AquaQuake™

M510BB ADDITIONAL FEATURES

- AIS receive
- DSC remote control (EN 300 338-8 compatible)
- Voice recording function

COMES WITH

- CommandMic (HM-195GB/GW)
- Connection cable (OPC-1540, 6.1 m, 20 ft)
- Connector cap
- DC power cable
- Microphone hanger
- Mounting base
- Warranty: 3 years

IPX7

M4100BB & M510BB

VHF Fixed Mount

Configurations

Model	Description	MSRP
M410BB 11 USA	Black box marine VHF fixed mount with black HM-195GB and two CommandMic ports.	\$1,029.00
M410BB GW 11 USA	Black box marine VHF fixed mount with white HM-195GW and two CommandMic ports.	\$1,029.00
M510BB 21 USA	Black box marine VHF fixed mount with AIS, black HM-195GB, and three CommandMic ports	\$1,249.00
M510BB GW 21 USA	Black box marine VHF fixed mount with AIS, white HM-195GW, and three CommandMic ports	\$1,249.00

Accessories

Model	Description	MSRP
Antennas		
UX241	GPS antenna	\$59.00
External Speakers		
SP37	30W hailer/speaker for fixed mounts; 4 ohm, extra UV protecting, all stainless steel hardware, heavy duty mounting bracket	\$76.00
Microphones		
HM195B 41 EXP	CommandMic IV with yellow backlit LCD in black	\$269.00
HM195GB 61 EXP	CommandMic IV with white backlit LCD in black	\$269.00
HM195GW 62 EXP	CommandMic IV with white backlit LCD in super white	\$269.00
HM195SW 42 EXP	Command Mic IV with yellow backlit LCD in super white	\$269.00
OPC1540	6.1m/20ft connection cable to use with the COMMANDMIC III/IV (mounting hardware required)	\$95.00
OPC1541	6.1m/20ft extension cable to use with the COMMANDMIC III/IV with the OPC1540. Up to 2 OPC-1541 can be connected.	\$81.00
Navigation		
MA510TR 13	AIS transponder with GPS navigation function, and NMEA 2000 connectivity.	\$1,418.00

M424G

VHF GPS Fixed Mount

SPECS

Output Power:	25W, 1W
Waterproof Rating:	IPX7 (submersible protection)
Frequencies:	Tx: 156.025–157.425MHz Rx: 156.050–163.275MHz
Usable Channel Groups:	USA, CAN, INT, WX
Type of Emission:	FM (16K0G3E) DSC (16K0G2B)
Current Drain:	Tx 25W output: 5.5A Rx AF Max External SP: 5.0A Internal SP: 1.5A
Weight:	2.65lb



FEATURES

- Built-in GPS
- Active noise canceling
- 10W loud audio, public address and foghorn
- Built-in class D DSC
- Optional COMMANDMICIV™ HM195B/SW or HM195GB/GSW
- Common GPS/NAV interface
- MarineCommander™ compatible
- MA-500TR AIS transponder compatible
- AquaQuake™ water draining function
- Weather channel with alert function
- Dualwatch and Tri-watch functions for monitoring Ch.16 and/or call channel
- Priority and normal scan
- Built-in attenuator for local communication

COMES WITH

- Hand microphone (HM-205)
- DC power cable
- Mounting bracket kit
- Owner's manual
- Warranty: 3 years

IPX7

M424G

VHF GPS Fixed Mount

Configurations

Model	Description	MSRP
M424G BLACK	Black fixed mount	\$499.00
M424G WHITE	Super white fixed mount	\$499.00

Accessories

Model	Description	MSRP
External Speakers		
SP24	External speaker (4x4") for marine fixed mount radios (7W)	\$61.00
SP35	5W external speaker with 3.5mm speaker jack and 2m cable	\$64.00
SP37	30W hailer/speaker for fixed mounts; 4 ohm, extra UV protecting, all stainless steel hardware, heavy duty mounting bracket	\$76.00
Microphones		
HM195B 41 EXP	CommandMic IV with yellow backlit LCD in black	\$269.00
HM195GB 61 EXP	CommandMic IV with white backlit LCD in black	\$269.00
HM195GW 62 EXP	CommandMic IV with white backlit LCD in super white	\$269.00
HM195SW 42 EXP	Command Mic IV with yellow backlit LCD in super white	\$269.00
HM196B	Standard hand microphone for M424 and works with the M424G	\$89.00
HM196SW	Standard hand microphone for M424 and works with the M424G	\$89.00
HM205B	Speaker microphone M424G/M506	\$91.00
OPC1540	6.1m/20ft connection cable to use with the COMMANDMIC III/IV (mounting hardware required)	\$95.00
OPC1541	6.1m/20ft extension cable to use with the COMMANDMIC III/IV with the OPC1540. Up to 2 OPC-1541 can be connected.	\$81.00
Mounting Hardware		
MB132	Flush mount kit for M324/M424G/MA510TR	\$42.00
Navigation		
MA510TR 13	AIS transponder with GPS navigation function, and NMEA 2000 connectivity.	\$1,418.00
Software & Cables		
CSM92D/M424	Programming software for M92D & M424	\$0.00
OPC478UD	USB programming cable (2-pin connectors handhelds)	\$95.00
OPC980	Cloning cable adapter for M424/M504/M604/M510	\$40.00

M510

VHF Fixed Mount

SPECS

Output Power:	25W or 1W (at 13.8V DC)
Waterproof Rating:	IPX8
Frequencies:	Tx: 156.025–157.425MHz Rx: 156.050–163.275MHz DSC: 156.525MHz AIS1, 2: 161.975, 162.025
Usable Channels:	USA, INT, CAN, and WX
Type of Emission:	16K0G3E (FM), 16K0G2B (DSC) 16K0GXW (AIS)*
Current Drain:	Tx 25W output: 5.0A Rx Max. audio: 3.3 A Rx AF Max External SP
Weight	1.6 lb without hand microphone
Versions	Radio without AIS receiver Radio with AIS receiver

*AIS version only



FEATURES

- Optional CT-M500 with NMEA 2000™
- Optional 25W two-way hailer/foghorn use with CT-M500
- Remote radio control/intercom with smart devices via RS-M500
- MMSI reset dongle
- Internal GPS built-in, option to use external GPS
- Slim 2.1 in depth design
- Active noise cancelling
- Full color, 3.5 in TFT LCD display
- Wide viewing angle
- Simplified navigation function with waypoints/AIS targets

COMES WITH

- Hand microphone (HM205-RB)
- DC power cable
- Mounting bracket kit
- Microphone hanger

IPX8

M510

VHF Fixed Mount

Configurations

Model	Description	MSRP
M510 11 USA	VHF fixed mount; class D DSC, no AIS	\$1,048.00
M510 PLUS 21 USA	VHF fixed mount; class D DSC, with AIS	\$1,206.00

Accessories

Model	Description	MSRP
MBF9	Flush mount kit for the M510/M510 EVO	\$53.00

Antennas

UX241	GPS antenna	\$59.00
-------	-------------	---------

Encryption & Internal Modules

UT112	Digital voice scrambling unit - 32 Codes	\$171.00
-------	--	----------

External Speakers

SP37	30W hailer/speaker for fixed mounts; 4 ohm, extra UV protecting, all stainless steel hardware, heavy duty mounting bracket	\$76.00
------	--	---------

Microphones

HM195B 41 EXP	CommandMic IV with yellow backlit LCD in black	\$269.00
HM195GB 61 EXP	CommandMic IV with white backlit LCD in black	\$269.00
HM195GW 62 EXP	CommandMic IV with white backlit LCD in super white	\$269.00
HM195SW 42 EXP	Command Mic IV with yellow backlit LCD in super white	\$269.00
HM205RB	Speaker microphone for M506 rear connector & M605	\$121.00
OPC1000	6.1m/20ft connection cable to use with the HM126RB/RG/HM205RB/HM157 (mounting hardware included)	\$86.00
OPC1540	6.1m/20ft connection cable to use with the COMMANDMIC III/IV (mounting hardware required)	\$95.00
OPC1541	6.1m/20ft extension cable to use with the COMMANDMIC III/IV with the OPC1540. Up to 2 OPC-1541 can be connected.	\$81.00

Miscellaneous

MBZ1	Screen cover for the M510	\$25.00
------	---------------------------	---------

Mounting Hardware

MBF7	Flush mount kit for the M510	\$53.00
------	------------------------------	---------

Navigation

MA510TR 13	AIS transponder with GPS navigation function, and NMEA 2000 connectivity.	\$1,418.00
------------	---	------------

Software & Cables

CSM510	Programming software for the M510, requires the OPC-980 + OPC-478UC programming cables.	\$0.00
OPC478UD	USB programming cable (2-pin connectors handhelds)	\$95.00
OPC980	Cloning cable adapter for M424/M504/M604/M510	\$40.00

M510 EVO

VHF Fixed Mount

SPECS

Output Power:	25W or 1W (at 13.8V DC)
Waterproof Rating:	IP68
Frequencies:	Tx: 156.025–157.425MHz Rx: 156.050–163.275MHz DSC: 156.525MHz AIS 1: 161.975, AIS 2: 162.025
Usable Channels:	USA, INT, CAN, and WX
Type of Emission:	16K0G3E (FM), 16K0G2B (DSC) 16K0GXW (AIS)
Current Drain:	Tx 25W output: 5.0A Rx Max. audio: 1.6 A 2.0 A (w/HM-195) 4.0 A (w/ext SP) 7.3A (w/ext SP, RX hailer, and HM-195) Rx AF Max External SP
Weight	1.6 lb without hand microphone
Versions	Radio without AIS receiver Radio with AIS receiver

FEATURES

NMEA 2000™ and two-way hailer/foghorn connection
Remote radio control/intercom with smart devices via RS-M500
MMSI reset dongle
Internal GPS built-in, option to use external GPS
Active noise cancelling
Full color, 3.5 in TFT LCD display
Wide viewing angle
Simplified navigation function with waypoints/AIS targets



COMES WITH

Hand microphone (HM-205RB)
DC power cable
Mounting bracket kit
Microphone hanger
Flash mount gasket

M510 EVO

VHF Fixed Mount

Configurations

Model	Description	MSRP
M510 EVO 41 USA	VHF fixed mount; class D DSC, NMEA 2000™, no AIS	\$1,349.00
M510 PLUS EVO 51 USA	VHF fixed mount; class D DSC, NMEA 2000™, with AIS	\$1,499.00

Accessories

Model	Description	MSRP
MBF9	Flush mount kit for the M510/M510 EVO	\$53.00
Antennas		
UX241	GPS antenna	\$59.00
Encryption & Internal Modules		
UT112	Digital voice scrambling unit - 32 Codes	\$171.00
External Speakers		
SP37	30W hailer/speaker for fixed mounts; 4 ohm, extra UV protecting, all stainless steel hardware, heavy duty mounting bracket	\$76.00
Microphones		
HM195B 41 EXP	CommandMic IV with yellow backlit LCD in black	\$269.00
HM195GB 61 EXP	CommandMic IV with white backlit LCD in black	\$269.00
HM195GW 62 EXP	CommandMic IV with white backlit LCD in super white	\$269.00
HM195SW 42 EXP	Command Mic IV with yellow backlit LCD in super white	\$269.00
HM205RB	Speaker microphone for M506 rear connector & M605	\$121.00
OPC1000	6.1m/20ft connection cable to use with the HM126RB/RG/HM205RB/HM157 (mounting hardware included)	\$86.00
OPC1540	6.1m/20ft connection cable to use with the COMMANDMIC III/IV (mounting hardware required)	\$95.00
OPC1541	6.1m/20ft extension cable to use with the COMMANDMIC III/IV with the OPC1540. Up to 2 OPC-1541 can be connected.	\$81.00
Miscellaneous		
MBZ1	Screen cover for the M510	\$25.00
Mounting Hardware		
MBF7	Flush mount kit for the M510	\$53.00
Navigation		
MA510TR 13	AIS transponder with GPS navigation function, and NMEA 2000 connectivity.	\$1,418.00
Software & Cables		
OPC478UD	USB programming cable (2-pin connectors handhelds)	\$95.00
OPC980	Cloning cable adapter for M424/M504/M604/M510	\$40.00

M605

VHF Fixed Mount

SPECS

Output Power:	25W, 1W
Waterproof Rating:	IPX8
Frequencies:	Tx: 156.025–161.600 MHz Rx: 156.025–162.000 MHz CH70: 156.525 MHz Ais1, 2: 161.975, 162.025 MHz
Usable Channel Groups:	USA, CAN, INT and WX
Type of Emission:	16K0G3E (FM), 16K0G2B (DSC)
Current drain:	Tx (at 25W output): 6.0A Rx (Maximum audio): 8.0A
Weight:	3.30lb
Versions:	Radio without AIS receiver Radio with AIS receiver



FEATURES

- 30W listen back hailer
- Built-in horn/foghorn
- GNSS antenna included
- Configuration flexibility
 - M605 + three COMMANDMICS
 - M605 + two COMMANDMICS + one Command Head
 - M605 + two Command Heads + one COMMANDMIC
- 4.3" wide color TFT LCD
- Night mode ensures readability in dark places
- Intuitive user interface
- NMEA2000™ and NMEA0183 connectivity
- Class D DSC
- Active noise cancelling
- Last call voice recording

COMES WITH

- Radio
- Hand microphone (HM-205RB)
- GNSS antenna (UX-241)
- PC power cable
- Mounting bracket kit
- Warranty: 3 years

IPX8

M605

VHF Fixed Mount

Configurations

Model	Description	MSRP
M605 31 USA	VHF fixed mount with color display and rear mic connector	\$1,286.00
M605 41 USA	VHF fixed mount with AIS, color display, and rear mic connector	\$1,607.00

Accessories

Model	Description	MSRP
Antennas		
UX241	GPS antenna	\$59.00
Command Head		
OPC2377	32.8ft extension cable for RC-M600	\$97.00
RCM600	Command head for M605. Comes with OPC-2383 & HM-205RB.	\$683.00
Encryption & Internal Modules		
UT112	Digital voice scrambling unit - 32 Codes	\$171.00
External Speakers		
SP24	External speaker (4x4") for marine fixed mount radios (7W)	\$61.00
SP35	5W external speaker with 3.5mm speaker jack and 2m cable	\$64.00
SP37	30W hailer/speaker for fixed mounts; 4 ohm, extra UV protecting, all stainless steel hardware, heavy duty mounting bracket	\$76.00
Microphones		
HM195B 41 EXP	CommandMic IV with yellow backlit LCD in black	\$269.00
HM195GB 61 EXP	CommandMic IV with white backlit LCD in black	\$269.00
HM195GW 62 EXP	CommandMic IV with white backlit LCD in super white	\$269.00
HM195SW 42 EXP	Command Mic IV with yellow backlit LCD in super white	\$269.00
HM205RB	Speaker microphone for M506 rear connector & M605	\$121.00
OPC1000	6.1m/20ft connection cable to use with the HM126RB/RG/HM205RB/HM157 (mounting hardware included)	\$86.00
OPC1540	6.1m/20ft connection cable to use with the COMMANDMIC III/IV (mounting hardware required)	\$95.00
OPC1541	6.1m/20ft extension cable to use with the COMMANDMIC III/IV with the OPC1540. Up to 2 OPC-1541 can be connected.	\$81.00
OPC2384	12-pin to 8-pin conversion cable to connect HM195 to M605 (1 cable required per HM195)	\$54.00
OPC999	20ft extension cable to connect COMMANDMIC II or HM-205RB to the OPC1000 and radio. Connect up to two HM205RB with M506 or one with M605.	\$59.00
Miscellaneous		
UX251	AIS receiver unit for the M605	\$268.00
Mounting Hardware		
MB75	Flush mount kit for mounting controller or speaker to a panel for M506/M605/M802/M504/M604/MA510TR/M502/M602	\$42.00
Navigation		
MA510TR 13	AIS transponder with GPS navigation function, and NMEA 2000 connectivity.	\$1,418.00

M605

VHF Fixed Mount

Accessories

Model	Description	MSRP
Software & Cables		
CSM605	Programming software for the M605. Includes MMSI reset dongle. Requires OPC2382 + OPC478UC for programming.	\$0.00
OPC2382	Conversion cable to program M605 (links OPC478UC to M605)	\$29.00
OPC478UD	USB programming cable (2-pin connectors handhelds)	\$95.00

HM195/G

COMMANDMIC™ IV Remote-Control Microphone

HM195B/SW – Orange backlighting

HM195GB/GW – White backlighting

Total control of all communications and Class D DSC functions.

Menu system provides easy and intuitive operation.

The bottom line of the dot-matrix display shows the software key functions, which can be toggled with the left and right buttons.

The directional keypad allows you to perform various operations and settings

IPX7 Submersible rating

Superior audio performance

AquaQuake™

Size (W x H x D): 2.66 x 5.69 x 1.46 in.

Weight (approx.; except cables): 14.1 oz

Supplied accessories:

- 20ft connection cable (OPC-1540)
- Mounting hardware for OPC-1540
 - Connector cap (part#8930069360)
 - Five screws (part#8810010710)
 - C-plate (part#8930069220)
 - Mic hanger (part#8950006870)



Configurations

Model	Description	MSRP
HM195GB 61 EXP	CommandMic IV with white backlit LCD in black	\$269.00
HM195GW 62 EXP	CommandMic IV with white backlit LCD in super white	\$269.00
HM195B 41 EXP	CommandMic IV with yellow backlit LCD in black	\$269.00
HM195SW 42 EXP	Command Mic IV with yellow backlit LCD in super white	\$269.00

Accessories

Model	Description	MSRP
Microphones		
OPC1540	6.1m/20ft connection cable to use with the COMMANDMIC III/IV (mounting hardware required)	\$95.00
OPC1541	6.1m/20ft extension cable to use with the COMMANDMIC III/IV with the OPC1540. Up to 2 OPC-1541 can be connected.	\$81.00
OPC2384	12-pin to 8-pin conversion cable to connect HM195 to M605 (1 cable required per HM195)	\$54.00

SSB



M803

HF Marine SSB

SPECS

Frequencies:

Tx: 1.6–2.9999, 4.0–4.9999,
6.0–6.9999, 8.0–8.9999,
12.0–13.9999, 16.0–17.9999,
18.0–19.9999, 22.0–22.9999,
25.0–27.5000MHz

Rx: 0.5–29.9999MHz (continuous)

DSC: 2.1875, 4.2075, 6.3120,
8.4145, 12.5770, 16.8045MHz

Mode:

Tx/Rx: J3E (USB, LSB), J2B (AFSK),
F1B (FSK), A1A (CW), H3E'
(AM) (' H3E receive only)

DSC: J2B

Current drain (at 13.6 V DC):

Receive: Less than 3.0 A (Maximum
audio output)

Transmit: 30 A (Maximum output power)

Weight:

Main unit 9.7lb

Controller 1.7lb



FEATURES

Emergency distress button

Intuitive user interface

Large main dial and software keys at the bottom of the display, provide
simple operation and easy access to often used functions

4.3" wide color TFT display

Night mode display

Integrated GPS receiver includes GPS, GLONASS, and SBAS function

Two minute instant replay function

Advance RF direct sampling system

HF e-mail ready

IPX7 waterproof remote controller

NMEA 0183 version 4.10 data input/output (4800-38400bps)

COMES WITH

Remote controller

PC power cable

Remote control cable

GPS antenna (16.4ft)

Microphone (HM214H)

Mounting bracket kits

ACC plugs & spare fuses

Owner's manual

Warranty: 2 years

M803

HF Marine SSB

Configurations

Model	Description	MSRP
M803	150W advanced SSB with Class E DSC MF/HF certification	\$4,043.00

Accessories

Model	Description	MSRP
Antenna Tuners		
AT140	HF automatic antenna tuner	\$767.00
OPC1465	32.8ft shielded control cable from AT140 to M803	\$92.00
Antennas		
AH710	Folded dipole antenna with an SO-239 connector. Covers 1.9 to 30MHz band. Length is approx 80.3ft.	\$525.00
External Speakers		
SP24	External speaker (4x4") for marine fixed mount radios (7W)	\$61.00
Microphones		
HM214H	Hand microphone for GM800 & M803	\$101.00
Mounting Hardware		
MB75	Flush mount kit for mounting controller or speaker to a panel for M506/M605/M802/M504/M604/MA510TR/M502/M602	\$42.00
Software & Cables		
OPC478UD	USB programming cable (2-pin connectors handhelds)	\$95.00

GMDSS



GM1600

Survival Craft VHF Handheld

SPECS

Output Power:	2W, 1W
Frequencies:	156.300-156.875MHz Rx: 156.050-163.275MHz
Type of Emission:	FM (16K0G3E)
Current Drain:	Tx 2W output: 1.0A 1W output: 0.7A Rx AF max: 200mA
Weight:	13.6oz (with BP234)



FEATURES

- Meets the strict environmental requirements for survival craft radio
- High capacity Lithium battery, BP234, has superior low temperature
- Large keypad with positive button action
- Wide viewing angle LCD display
- One touch access to Channel 16 and call channel
- Highly visible yellow colored body
- Bright LED indicator on the top of panel
- Optional VOX headset for on-board use

COMES WITH

- GM1600DU 71 USA:
 - Battery pack (BP252)
 - Battery pack (BP234)
 - Battery charger (BC173)
 - AC adapter (BC147SA)
 - Belt clip (MB103Y)
 - Antenna (FAS61V)
 - Neck strap
 - Owner's manual
 - Warranty: 3 years

- GM1600SC 71 USA:
 - Battery pack (BP234)
 - Belt clip (MB103Y)
 - Antenna (FAS61V)
 - Neck strap
 - Owner's manual
 - Warranty: 3 years

GM1600

Survival Craft VHF Handheld

Configurations

Model	Description	MSRP
GM1600SC 71 USA	GMDSS VHF handheld for survival crafts; radio plus BP-234 lithium battery	\$1,050.00
GM1600DU 71 USA	GMDSS VHF handheld for survival crafts; includes li-ion battery/charger plus the BP-234 battery. Surface shipping only.	\$1,145.00

Accessories

Model	Description	MSRP
Antennas		
FAS61V	Standard antenna for GM1600	\$18.00
Batteries		
BP234	9.0V 3300mAh lithium battery pack GM1600. FedEx ground shipping only. No shipments to HI or AK.	\$268.00
BP252	7.4V 980mAh Li-Ion battery (M36/M34/GM1600)	\$78.00
Belt Clips		
MB103Y	Yellow alligator belt clip for the GM1600	\$16.00
MB86	Swivel belt clip that screws into back of radio	\$14.00
MB96N	Swivel belt hanger to use with belt clip	\$40.00
Cables		
OPC515L	DC power cable for single unit rapid chargers	\$28.00
Chargers		
AD109	Adapter cup fits the BC119N/BC121N and charges the BP224 (M90/GM1600)	\$19.00
BC123SE	AC adapter for rapid chargers; 100-240V with Euro style plug	\$28.00
BC147SA	AC adapter for trickle chargers; 100-240V with a US style plug	\$23.00
BC147SE 15	AC adapter for trickle chargers; 230V with a Euro style plug	\$17.00
BC157S	AC adapter for gang chargers; 100-240V with US style plug	\$168.00
BC173 01	Desktop trickle charger (M34/M36/GM1600/BP224) requires BC-147S	\$32.00
CP23L	12V cigarette lighter cable for use with rapid chargers	\$40.00
Headsets		
HS94	Earpiece headset; use with VS/OPC2004/OPC2006/OPC1392	\$27.00
HS95	Headset with boom mic; use with VS/OPC2004/OPC2006/OPC1392	\$230.00
HS97	Earphone with throat mic headset; use with VS/OPC2004/OPC2006/OPC1392	\$45.00
OPC1392	Headset adapter to use with HS94/95/97 for the M73/M72/GM1600/M90	\$81.00
Microphones		
HM167	Lightweight IPX8 waterproof speaker mic M73/GM1600/M92/M72	\$131.00
Software & Cables		
CSGM1600	GM1600 programming software	\$0.00
OPC478UD	USB programming cable (2-pin connectors handhelds)	\$95.00

AIS & Radars



MA510TR

Class B AIS Transponder

SPECS

Output Power:	2W
Waterproof Rating:	IPX7
Frequencies:	161.500-162.025MHz
Type of Emission:	16K0G2B
Weight:	1.5lb
DATA Interface:	
USB (Type-B Mini):	GGA, GNS, GLL, GSA, GSV, RMC, VTG, VDM, VDO, ACA, ACS, ALR, TXT
NMEA 2000™	
Input:	059392 /904, 060160 /416 /928, 065240, 126208 /996, 129026 /029 /545
Output:	059392 /904,060416 /928,126208 /464 /993 /996 /998, 129026 /029 /038 /039 /040 /041 /539 /540 /545 /792 /793 /794 /797 /798 /801 /802 /803 /805 /806 /807 /809 /810 /811
NMEA 0183	
Input/Output	4800–38400 bps; Sentence Format: GGA, GNS, GLL, GSA*1, GSV*1, RMC, VTG, GBS, DTM, DSC
External GPS Input:	4800–38400 bps, Sentence format: GGA, GNS, GLL, RMC, VTG, GBS*2, DTM
AIS Output:	38400 bps, Sentence format: VDM, VDO, ACA, ACS, ALR, TXT

*1 Only 38400 bps.

*2 When a received GPS signal does not include a GBS sentence, the transponder will not receive the signal from the external GPS receiver

FEATURES

Class B AIS transponder, receives both A & B signals
Large 4.3" Color TFT LCD Display
Night Screen mode
Wide angle viewing
NMEA 2000™, 0183/-HS connectivity
Built-in simple navigation function
100 waypoint memory
Friend/danger nav function
Silent mode
Individual DSC call
USB connectivity
Multi-lingual user interface
12V and 24V
Collision alarm function
Anchor watch alarm
Man over board (MOB) function, assignable MOB waypoint



COMES WITH

Speaker Microphone
GPS Antenna Unit

MA510TR

Class B AIS Transponder

Configurations

Model	Description	MSRP
MA510TR 13	AIS transponder with GPS navigation function, and NMEA 2000 connectivity.	\$1,418.00

Accessories

Model	Description	MSRP
<i>Mounting Hardware</i>		
MB132	Flush mount kit for M324/M424G/MA510TR	\$42.00
MB75	Flush mount kit for mounting controller or speaker to a panel for M506/M605/M802/M504/M604/MA510TR/M502/M602	\$42.00

MR-1010R2

Marine Radar

SPECS

Display Type:	10.4-inch Color TFT LCD
Resolution:	480 x 640 dots
Type of Emission:	16K0G3E (FM)
Minimum Range:	25m; 82ft (at 1/8 NM range)
Maximum Range:	36 NM



FEATURES

- Connect to a DSC radio to use the DSC information function
- Connect to an external AIS device to use the AIS overlay function
- Large color display with an approximate 176° viewing angle
- Color RFT LCD (480x640 dots) display offers bright vivid echos with 16 steps gradient intensity
- Easily adjust the screen color (day, night and user settings) with the "BRILL" button
- Language setting is selectable from English, Indonesian, Korean, Spanish, Thai and Vietnamese
- Simplified ARPA function helps prevent collision risk with other vessels or objects
- TLL (Target Latitude Longitude) function
- True trail function
- 10.2-42V wide DC input to prevent over voltage damage
- Two user programmable alarm zones
- Optional video output unit

MR-1010R2

Marine Radar

Configurations

Model	Description	MSRP
MR1010R2 13	Marine radar, 4kW, color LCD - US version	\$4,399.00

Accessories

Model	Description	MSRP
Miscellaneous		
UX252	Analog TCG output for the MR1010R2II	\$294.00

Discontinued Radios



M93D

VHF Marine Transceiver are discontinued and no longer available from Icom. Icom does still sell the below compatible accessories.

Accessories

Model	Description	MSRP
Antennas		
FASC59V	Standard antenna M25/M37/M93D/M92D	\$24.00
Batteries		
BP285	Li-ion 7.2V 1570mAh (typical), 1485mAh (minimum) battery for M93D	\$118.00
Belt Clips		
MB133	Alligator type belt clip	\$18.00
Cables		
OPC515L	DC power cable for single unit rapid chargers	\$28.00
Chargers		
BC123SA	Straight-angle AC adapter for rapid chargers; 100-240V with US style plug	\$26.00
BC123SE	AC adapter for rapid chargers; 100-240V with Euro style plug	\$28.00
BC157S	AC adapter for gang chargers; 100-240V with US style plug	\$168.00
BC157SE	AC adapter for gang chargers; 100-240V with Euro style plug	\$168.00
BC214 14	Gang charger for the M93D. Includes the BC157.	\$541.00
BC220	Rapid charger for the M93D, charging cable sold separately.	\$69.00
CP23L	12V cigarette lighter cable for use with rapid chargers	\$40.00
Microphones		
HM165	Waterproof speaker mic for M34/M36/M93D/M94D	\$118.00
HM228	Compact IPX7 speaker mic for M93D/M94D/IP110H	\$103.00
Software & Cables		
OPC1655	Cloning cable adapter for M25/M36/M37/M93D/M94D	\$50.00
OPC478UD	USB programming cable (2-pin connectors handhelds)	\$95.00

M36

The M36 VHF Marine Transceivers are discontinued and no longer available from Icom. Icom does still sell the below compatible accessories

Accessories

Model	Description	MSRP
Antennas		
FASC58V	Standard antenna M24/M34/M36/M85	\$18.00
Batteries		
BP251	Alkaline case for M34/M36 (5 x AAA)	\$41.00
BP252	7.4V 980mAh Li-Ion battery (M36/M34/GM1600)	\$78.00
Belt Clips		
MB109	Belt clip for the M34/M36/M92D	\$11.00
Cables		
OPC515L	DC power cable for single unit rapid chargers	\$28.00
Chargers		
BC123SE	AC adapter for rapid chargers; 100-240V with Euro style plug	\$28.00
BC147SA	AC adapter for trickle chargers; 100-240V with a US style plug	\$23.00
BC147SE 15	AC adapter for trickle chargers; 230V with a Euro style plug	\$17.00
BC173 01	Desktop trickle charger (M34/M36/GM1600/BP224) requires BC-147S	\$32.00
CP23L	12V cigarette lighter cable for use with rapid chargers	\$40.00
Microphones		
HM165	Waterproof speaker mic for M34/M36/M93D/M94D	\$118.00
Software & Cables		
OPC1655	Cloning cable adapter for M25/M36/M37/M93D/M94D	\$50.00
OPC478UD	USB programming cable (2-pin connectors handhelds)	\$95.00

M604

The M604 VHF Marine Transceivers are discontinued and no longer available from Icom. Icom does still sell the below compatible accessories.

Configurations

Model	Description	MSRP
M605 31 USA	VHF fixed mount with color display and rear mic connector	\$1,286.00
M605 41 USA	VHF fixed mount with AIS, color display, and rear mic connector	\$1,607.00

Accessories

Model	Description	MSRP
Antennas		
UX241	GPS antenna	\$59.00
Cables		
OPC1174	M602/M604 DC power cord	\$15.00
Command Head		
OPC2377	32.8ft extension cable for RC-M600	\$97.00
RCM600	Command head for M605. Comes with OPC-2383 & HM-205RB.	\$683.00
Encryption & Internal Modules		
UT112	Digital voice scrambling unit - 32 Codes	\$171.00
External Speakers		
SP24	External speaker (4x4") for marine fixed mount radios (7W)	\$61.00
SP35	5W external speaker with 3.5mm speaker jack and 2m cable	\$64.00
SP37	30W hailer/speaker for fixed mounts; 4 ohm, extra UV protecting, all stainless steel hardware, heavy duty mounting bracket	\$76.00
Microphones		
HM126RB	Standard black rear mount mic for M504/M604	\$116.00
HM195B 41 EXP	CommandMic IV with yellow backlit LCD in black	\$269.00
HM195GB 61 EXP	CommandMic IV with white backlit LCD in black	\$269.00
HM195GW 62 EXP	CommandMic IV with white backlit LCD in super white	\$269.00
HM195SW 42 EXP	Command Mic IV with yellow backlit LCD in super white	\$269.00
HM205RB	Speaker microphone for M506 rear connector & M605	\$121.00
OPC1000	6.1m/20ft connection cable to use with the HM126RB/RG/HM205RB/HM157 (mounting hardware included)	\$86.00
OPC1540	6.1m/20ft connection cable to use with the COMMANDMIC III/IV (mounting hardware required)	\$95.00
OPC1541	6.1m/20ft extension cable to use with the COMMANDMIC III/IV with the OPC1540. Up to 2 OPC-1541 can be connected.	\$81.00
OPC2384	12-pin to 8-pin conversion cable to connect HM195 to M605 (1 cable required per HM195)	\$54.00
OPC999	20ft extension cable to connect COMMANDMIC II or HM-205RB to the OPC1000 and radio. Connect up to two HM205RB with M506 or one with M605.	\$59.00
Miscellaneous		
UX251	AIS receiver unit for the M605	\$268.00
Mounting Hardware		
M602 MMB	Black mounting bracket M602 01	\$30.00

Accessories

Model	Description	MSRP
MB75	Flush mount kit for mounting controller or speaker to a panel for M506/M605/M802/M504/M604/MA510TR/M502/M602	\$42.00
Navigation		
MA510TR 13	AIS transponder with GPS navigation function, and NMEA 2000 connectivity.	\$1,418.00
Software & Cables		
CSM605	Programming software for the M605. Includes MMSI reset dongle. Requires OPC2382 + OPC478UC for programming.	\$0.00
OPC2382	Conversion cable to program M605 (links OPC478UC to M605)	\$29.00
OPC478UD	USB programming cable (2-pin connectors handhelds)	\$95.00
OPC980	Cloning cable adapter for M424/M504/M604/M510	\$40.00

M802

HF Marine Transceiver are discontinued and no longer available from Icom. Icom does still sell the below compatible accessories.

Accessories

Model	Description	MSRP
Antenna Tuners		
AT140	HF automatic antenna tuner	\$767.00
OPC1147N	Shielded control cable to connect the M802 to the AT140 (10m)	\$84.00
Antennas		
AH710	Folded dipole antenna with an SO-239 connector. Covers 1.9 to 30MHz band. Length is approx 80.3ft.	\$525.00
Cables		
OPC1107A	M802 Main Unit DC PC	\$29.00
External Speakers		
SP24	External speaker (4x4") for marine fixed mount radios (7W)	\$61.00
Microphones		
HM135N	Hand microphone; water resistant, remote function for M802	\$199.00
Mounting Hardware		
M802 MMB	Mounting Bracket M802	\$57.00
MB75	Flush mount kit for mounting controller or speaker to a panel for M506/M605/M802/M504/M604/MA510TR/M502/M602	\$42.00
Remote Mounting		
OPC1106	Seperation cable between controller and main unit (16.4ft) for M802	\$47.00
Software & Cables		
CSM802	M802 Program Software	\$0.00
OPC478UD	USB programming cable (2-pin connectors handhelds)	\$95.00

M506

VHF Marine Transceiver are discontinued and no longer available from Icom. Icom does still sell the below compatible accessories.

Accessories

Model	Description	MSRP
Encryption & Internal Modules		
UT112	Digital voice scrambling unit - 32 Codes	\$171.00
External Speakers		
SP24	External speaker (4x4") for marine fixed mount radios (7W)	\$61.00
SP35	5W external speaker with 3.5mm speaker jack and 2m cable	\$64.00
SP37	30W hailer/speaker for fixed mounts; 4 ohm, extra UV protecting, all stainless steel hardware, heavy duty mounting bracket	\$76.00
Microphones		
HM195B 41 EXP	CommandMic IV with yellow backlit LCD in black	\$269.00
HM195GB 61 EXP	CommandMic IV with white backlit LCD in black	\$269.00
HM195GW 62 EXP	CommandMic IV with white backlit LCD in super white	\$269.00
HM195SW 42 EXP	Command Mic IV with yellow backlit LCD in super white	\$269.00
HM205B	Speaker microphone M424G/M506	\$91.00
HM205RB	Speaker microphone for M506 rear connector & M605	\$121.00
OPC1000	6.1m/20ft connection cable to use with the HM126RB/RG/HM205RB/HM157 (mounting hardware included)	\$86.00
OPC1540	6.1m/20ft connection cable to use with the COMMANDMIC III/IV (mounting hardware required)	\$95.00
OPC1541	6.1m/20ft extension cable to use with the COMMANDMIC III/IV with the OPC1540. Up to 2 OPC-1541 can be connected.	\$81.00
OPC999	20ft extension cable to connect COMMANDMIC II or HM-205RB to the OPC1000 and radio. Connect up to two HM205RB with M506 or one with M605.	\$59.00
Mounting Hardware		
MB132	Flush mount kit for M324/M424G/MA510TR	\$42.00
MB75	Flush mount kit for mounting controller or speaker to a panel for M506/M605/M802/M504/M604/MA510TR/M502/M602	\$42.00
Navigation		
MA510TR 13	AIS transponder with GPS navigation function, and NMEA 2000 connectivity.	\$1,418.00
Software & Cables		
CSM506	M506 programming software. Requires OPC-478UC + OPC-980 cables.	\$0.00
OPC478UD	USB programming cable (2-pin connectors handhelds)	\$95.00
OPC980	Cloning cable adapter for M424/M504/M604/M510	\$40.00



U.S. Marine Retail
Price Book

Icom America Inc.